Printing date 17.12.2018 Version No. 2 Revision: 17.12.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Pallmann Spritzkork
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use

SU19 Building and construction work

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) For professional use only.

- · Product category PC1 Adhesives, sealants
- · Application of the substance / the mixture Sealant
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

PALLMANN GmbH

Im Kreuz 6

D-97076 Würzburg

Tel. +49 (0)931-27964-0

Fax +49 (0)931-27964-50

· Further information obtainable from:

Products Development Lab E-Mail: msds.info@uzin-utz.com

· 1.4 Emergency telephone number:

Medical emergencies (GIZ-Nord Poisons Center): +49 551 19240

Transportation emergencies: +49 621 60 43 333

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- · Hazard pictograms GHS02, GHS07, GHS09
- · Signal word Danger
- · Hazard-determining components of labelling:

Naphtha (petroleum), hydrotreated light (<0,01% benzene)

· Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

(Contd. on page 2)

Trade name: Pallmann Spritzkork

(Contd. of page 1)

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P261 Avoid breathing vapours.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

P391 Collect spillage.

· 2.3 Other hazards

Polishing dust from oxygen-drying systems may be liable to spontaneous combustion. Danger of fire! (see chapt. 5, 7, 10, 13).

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description:

Solvent based joint adhesive solution for parquet flooring

Solvent mixture with additives

	· Dangerous components:		
	CAS: 64742-49-0	Naphtha (petroleum), hydrotreated light (<0,01% benzene)	50-75%
	EINECS: 265-151-9	♠ Flam. Liq. 2, H225; ♦ Asp. Tox. 1, H304; ♦ Aquatic Chronic 2, H411; ♠ Skin Irrit. 2, H315; STOT SE 3, H336	
L		•	
	CAS: 110-54-3	n-hexane	1-<3%
	EINECS: 203-777-6	♠ Flam. Liq. 2, H225; ♠ Repr. 2, H361f; STOT RE 2, H373; Asp. Tox. 1, H304; ♠ Aquatic Chronic 2, H411; ♠ Skin Irrit. 2, H315;	
		Tox. 1, H304; (1) Aquatic Chronic 2, H411; (1) Skin Irrit. 2, H315;	
		STOT SE 3, H336	

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation:

Supply fresh air; consult doctor in case of complaints.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Do not induce vomiting; call for medical help immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- \cdot 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:

CO₂ powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

(Contd. on page 3)

Trade name: Pallmann Spritzkork

(Contd. of page 2)

· For safety reasons unsuitable extinguishing agents: Water with full jet

- 5.2 Special hazards arising from the substance or mixture Can form explosive gas-air mixtures.
- 5.3 Advice for firefighters
- · **Protective equipment:** Mouth respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

Ensure adequate ventilation

- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Wear suitable protective clothing, gloves and eye/face protection.

Immediately remove all soiled and contaminated clothing

Avoid contact with the eyes and skin.

Keep away from foodstuffs, beverages and feed.

Do not inhale gases / fumes / aerosols.

Wash hands before breaks and at the end of work.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

CAS: 110-54-3 n-hexane

WEL Long-term value: 72 mg/m³, 20 ppm

- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

(Contd. on page 4)

Trade name: Pallmann Spritzkork

(Contd. of page 3)

Wear suitable protective clothing, gloves and eye/face protection.

Avoid contact with the eyes and skin.

Keep away from foodstuffs, beverages and feed.

Do not inhale gases / fumes / aerosols.

Wash hands before breaks and at the end of work.

· Respiratory protection:

Not necessary in well ventilated areas or areas with local exhaust ventilation (e.g. ex-protected ventilation / evacuation equipment).

In case of prolonged exposition in poorly ventilated areas, e.g. in closed rooms, use ambient air-independent breathing apparatus.

· Protection of hands:



Use gloves of stable material (e.g. Nitrile) - if necessary tricoted to improve the wearability (EN 374)

· Material of gloves

Butyl rubber, BR

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.5 mm

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles (EN 166)

SECTION 9: Physical and chemical properties			
9.1 Information on basic physical and cl General Information	hemical properties		
· Appearance: Form:	Pasty		
Colour:	Light brown		
· Odour:	Solvent-like		
· Odour threshold:	Not determined.		
· pH-value:	Not determined.		
· Change in condition Melting point/freezing point: Initial boiling point and boiling range:	Undetermined. Undetermined.		
· Flash point:	-12 °C		
· Flammability (solid, gas):	Not applicable.		
· Ignition temperature:	240 °C		
Decomposition temperature:	Not determined.		
· Auto-ignition temperature:	Polishing dust from oxygen-drying systems may be liable to spontaneous combustion. Danger of fire! (see chapt. 5, 7, 10, 13).		
Explosive properties:	Product does not present an explosion hazard.		
· Explosion limits:			
Lower:	0.6 Vol %		
Upper:	7.0 Vol %		

(Contd. on page 5)

Printing date 17.12.2018 Version No. 2 Revision: 17.12.2018

Trade name: Pallmann Spritzkork

		(Contd. of page 4
· Vapour pressure at 50 °C:	390 hPa	
· Density at 20 °C:	0.60g/cm^3	
Relative density	Not determined.	
· Vapour density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
water:	Insoluble.	
Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity:		
Dynamic at 20 °C:	>50000 mPas	
Kinematic at 40 °C:	>100 s (ISO 6 mm)	
· 9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.

(Contd. on page 6)

Printing date 17.12.2018 Version No. 2 Revision: 17.12.2018

Trade name: Pallmann Spritzkork

(Contd. of page 5)

- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system.

Toxic for aquatic organisms

Also poisonous for fish and plankton in water bodies.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

The product contains materials that are harmful to the environment.

Do not allow product to reach ground water, water course or sewage system.

Let product residues harden in open container, then dispose of as construction waste.

Disposal should be in accordance with local, state or national legislation.

- · Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations.

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

14.1 UN-Number ADR, IMDG, IATA	UN1133
· 14.2 UN proper shipping name	
ADR	1133 ADHESIVES, ENVIRONMENTALLY HAZARDOUS
IMDG	ADHESIVES (Naphtha (petroleum), hydrotreated ligi (<0,01% benzene), HEXANES), MARINE POLLUTANT
· IATA	ADHESIVES
14.3 Transport hazard class(es)	
ADR, IMDG	
4 2	
3	
Class	3 Flammable liquids.
	3 Flammable liquids. 3
Class Label	
Label	
Label	

(Contd. on page 7)

Trade name: Pallmann Spritzkork

	(Contd. of page
· 14.4 Packing group · ADR, IMDG, IATA	III
14.5 Environmental hazards:	Product contains environmentally hazardous substance. Naphtha (petroleum), hydrotreated light (<0,01% benzene
· Marine pollutant: · Special marking (ADR):	Yes Symbol (fish and tree) Symbol (fish and tree)
· 14.6 Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	-
· EMS Number:	F- E , S - D
· Stowage Category	A
· 14.7 Transport in bulk according to Anne	ex II of
Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Transport category	3
· Tunnel restriction code	E
· UN "Model Regulation":	UN 1133 ADHESIVES, 3, III, ENVIRONMENTALL HAZARDOUS

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H361f Suspected of damaging fertility.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

- · Recommended restriction of use For professional use only.
- · Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· Contact:

Dr. Kötte, phone +49 (0)931 27964-25

E-Mail: msds.info@uzin-utz.com

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

(Contd. on page 8)

Printing date 17.12.2018 Version No. 2 Revision: 17.12.2018

Trade name: Pallmann Spritzkork

(Contd. of page 7)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Repr. 2: Reproductive toxicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

* Data compared to the previous version altered.