



TimberTech Neo Acoustic Underlay

Heavyweight crumb rubber underlay with **outstanding noise reduction.**

- Shhh! Underlay at work**
 TimberTech Neo Acoustic gives high insulation against impact sound - really bringing down noise levels and making the room a better place to be.
- Protects against moisture**
 The gold vapour barrier stops your floor covering being damaged by moisture rising up from the sub-floor.
- Old tyre, new life**
 TimberTech Neo Acoustic is made with rubber from recycled car tyres, which means old tyres don't go into landfill - so it's better for the planet.

Heavy Traffic

Wood



Technical Data

| Properties | Unit | Value | Method |
|-----------------------------------|------------------------------|---------------------|--|
| Thickness | mm | 5 | internal |
| Density | kg/m ³ | 400 ± 50 | internal |
| Weight per square metre | kg/m ² | 2.5 ± 10% | internal |
| Impact Sound Reduction | dB | ≥ 26 | BS EN ISO 717-2:2013 BS EN ISO 10140-3:2010 |
| Thermal Resistance | Tog | 1.03 | BS4745:2005 |
| Flammability (hot metal nut test) | Pass - low radius of effect* | BS 4790:1987 (2009) | |

*Values derived from similar products

The information given above may vary and is partly based on information from our suppliers. It represents the prevailing level of expertise and is not binding in a legal sense. The compliance of legal requirements lies within the customers own responsibility.

QA Flooring Solutions Ltd

Unit 2 Hurricane Drive

Liverpool L24 8RL

Tel: 0151 495 3434

Fax: 0151 427 0484

Email: sales@qaflooringsolutions.com

www.qaflooringsolutions.com

Simply Better

Best for

Cushioning

Moisture Protection

Sound Reduction

Hard Wearing

Compression Recovery

Underfloor Heating

Hard Wearing

Heat Insulation

Commercial Use

Available in

Code QAU-TNA-01

Size 1m x 8m (8m²)

Thickness 5mm