

Bona Polish Gloss

Technical data sheet

Professional
Floor Care



Bona Polish Gloss is a ready-to-use waterborne maintenance coating designed specifically for varnished wooden floors but possible to use on a variety of floor types. Being reinforced with polyurethane it leaves an exceptionally durable wear layer on the floor making it suitable for use in both domestic and commercial environments. Bona Polish Gloss gives the surface new lustre and continued protection against wear.

- Possible to use on a variety of floors including varnished floors, laminate, linoleum, PVC and ceramic tiles.
- Reinforced with polyurethane for increased durability.
- Excellent flow for a flawless surface
- Slip resistance compliant to DIN 18032:2.

Technical data

Binding agent:	Acrylate/Polyurethane
Sheen:	Gloss
Dilution:	Do not dilute, product is ready-to-use
Drying time:	≈ 1 hour (20°C/60% RH)
Application tools:	Bona Microfibre Applicator Pad
Coverage:	≈ 50 m ² /litre
Safety:	Unclassified, see safety data sheet for more details.
Cleaning:	Clean tools in soap and water. Dried stains can be removed with Bona Remover or acetone.
Shelf life:	2 years from the date of production, in unopened original container.
Storage/Transport:	The temperature must not fall below +5°C or exceed +25°C during storage and transport.
Disposal:	Wastes and emptied containers should be handled in accordance with local regulations.
Package size:	10 x 1 litre (50 boxes per pallet) 3 x 5 litres (44 boxes per pallet)

Preparations

Remove loose dirt and grit from floor. Clean floor thoroughly with Bona Cleaner to make sure that dirt will not be trapped in the coating. Let floor dry. Do not use polish on any floor that has been waxed or oiled. Wax and oil residues will prevent the proper adhesion of polish to the floor. **Always test on small area to verify proper adhesion and desired results prior to use.**

Application

1. Shake container thoroughly before use. Apply polish in a 3-4 cm wide wavy line on a 3 m² section of the floor and spread the product directly using a flat polish application pad such as the Bona Applicator Pad. For best results, apply a thin consistent coat.
2. Without adding more product, smooth out the section by pulling the applicator along the grain of the wood.
3. Continue with next section and then allow the ready treated floor minimum 1 hour drying time before resuming light foot traffic on the floor. If required, it is possible to apply a second layer of polish after 2 hours.



Bona[®]

Bona Polish Gloss

Technical data sheet

Professional
Floor Care



Avoid heavy traffic and the replacement of furniture and rugs until next day. To achieve a uniform aspect it is advised to always treat the entire surface.

Maintenance

Wetcleaning of the floor may be carried out after three days drying. For regular cleaning use Bona Cleaner. Do not use strongly alkaline cleaning agents as they may damage the floor or remove the protective coating of polish.

Tips

- When smoothing out the polish, maintain the applicator pad flat to the surface, going wall-to-wall. Avoid lifting the applicator along the way as this produces bubbles.
- Do not work into areas starting to dry as this may produce streaking.
- If applying multiple layers of polish. Do not stress the drying time between coats. Risk of dissolving previous layers.

Bona[®]