

Cleaner

CLEAN STRONG

Water-based basic cleaning agent thoroughly removing even strong contamination

PRODUCT DESCRIPTION:

Water-based cleaning product, which removes heavy soiling very well and thus creates the conditions for the subsequent initial care.

SUITABLE FOR:

- ▶ sealed wood/cork floors
- ▶ sealed multilayer wood floors
- ▶ PVC
- ▶ natural and synthetic stone floors



APPLICATION:

1. Before use, the container must be brought to room temperature (20 °C) and must be shaken well.
2. Apply PALLMANN CLEAN STRONG according to the degree of contamination.
3. Dilute approx. 20 - 50 ml PALLMANN CLEAN STRONG with 5 litres of water. Remove the dirt from the surface with a PALLMANN MOP, brush or PALLMANN UNO and CLEANING PAD GREEN.
4. Leave for approx. 2 - 5 minutes and then brush hard with a brush.
5. Remove the released contamination and rinse twice with clean water. For especially stubborn soiling, repeat if necessary.

PRODUCT BENEFITS / PROPERTIES:

- ▶ high dirt solubility

TECHNICAL DATA:

Packaging:	plastic container
Packsize:	0,75 and 10 l
Shelf life:	at least 24 months
Consumption:	approx. 20 - 50 ml/5 l water
Working climate:	between 18 – 25 °C and 35 – 65 % relative humidity

NOTE:

PALLMANN CLEAN STRONG if left too long on a sealed wood floor can begin to effect the performance of the sealer coat. Always conduct a test before proceeding.

IMPORTANT NOTES:

- ▶ Optimum temperature is 18 to 25 °C with the relative humidity > 35 % and < 65 %. Low temperatures and high humidity will extend the drying time. High temperatures and low humidity will shorten the drying time.
- ▶ Shelf life minimum 24 months in original packaging when stored in dry conditions. Protect from freezing and do not expose to temperatures over 40 °C.
- ▶ Tightly reseal opened containers.
- ▶ Leave freshly oiled surfaces until fully hardened before treating with PALLMANN CLEAN STRONG.
- ▶ Regular maintenance improves the appearance and increases the wear life of the sealed surface. Only damp (not wet). Avoid standing water.
- ▶ The following standards and notices are applicable and especially recommended: DIN 18356 "Working with parquet and woodblocks", DIN 18365 "Working with floor coverings".

PROTECTION OF THE WORKPLACE AND THE ENVIRONMENT:

Not flammable. Causes skin irritation/ serious eye damage. Keep out of reach of children. Avoid contact with eyes and skin. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. In case of contact with skin, wash immediately with plenty of water and soap. During application, use barrier cream and protective gloves and safety goggles. Observe safety information on product label as well as safety data sheet.

DISPOSAL:

Do not allow dispersal into drains, sewers or ground. Rinse containers, which have been emptied from any residues, with little water and dispose of the containers in accordance with local guidelines as recyclable packaging. Collect and reuse rinsing water and product remnants. If even necessary, dispose of containers with residues as well as product remnants as special waste.