

Material Safety Data Sheets
 according to 1907/2006/EC, Article 31

Printing date 23.05.2018

Version number 23

Revision: 08.05.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **Osmo Country Color**

Article number: 2101 White; 2203 Light Ochre; 2204 Ivory; 2205 Sunflower Yellow; 2308 Nordc Red; 2310 Cedar/Redwood; 2311 Signal Red; 2404 Fir Green; 2501 Labrador Blue; 2506 Royal Blue; 2507 Dove Blue; 2606 Medium Brown; 2607 Dark Brown; 2703 Charcoal; 2704 Dust Grey; 2708 Pebble Grey; 2716 Anthracite Grey ; 2735 Light Grey; 2742 Traffic Grey

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Coating compound/ Surface coating/ paint
 Paint

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Osmo Holz und Color GmbH & Co. KG
 Affhüppen Esch 12
 D-48231 Warendorf

Further information obtainable from:

Product safety department
 Phone: +49 (0) 251 / 692 - 188
 Fax: +49 (0) 251 / 692 - 462
 e-mail: helmut.starp@osmo.de

1.4 Emergency telephone number:

emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory service in German and English

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to

Regulation (EC) No 1272/2008 The product is not classified, according to the CLP regulation.

2.2 Label elements

Labelling according to Regulation

(EC) No 1272/2008 Void

Hazard pictograms Void

Signal word Void

Hazard statements Void

Precautionary statements If medical advice is needed, have product container or label at hand.
 Keep out of reach of children.

P262 Do not get in eyes, on skin, or on clothing.

P271 Use only outdoors or in a well-ventilated area.

Additional information: Observe the general safety regulations when handling chemicals.

Always wear a dust mask when sanding.

Safety data sheet available on request.

(Contd. on page 2)

Material Safety Data Sheets
 according to 1907/2006/EC, Article 31

Printing date 23.05.2018

Version number 23

Revision: 08.05.2018

Trade name: Osmo Country Color

(Contd. of page 1)

2.3 Other hazards

Warning:

Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition)

Results of PBT and vPvB assessment**PBT:** Not applicable.**vPvB:** Not applicable.**SECTION 3: Composition/information on ingredients****3.2 Mixtures****Description:** Mixture of substances listed below with nonhazardous additions.**Dangerous components:**

EC number: 918-481-9	aliphatic hydrocarbons, C10-C13	 Asp. Tox. 1, H304	25-50%
Index number: 649-327-00-6			
Reg.nr.: 01-2119457273-39			

Additional information:

For the wording of the listed hazard phrases refer to section 16.

The content of Titanium dioxide varies according to the colour shade.

SECTION 4: First aid measures**4.1 Description of first aid measures****General information:**

Immediately remove any clothing soiled by the product.

After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

After skin contact:

In case of unconsciousness place patient stably in side position for transportation.

Immediately wash with water and soap and rinse thoroughly.

After eye contact:

If skin irritation continues, consult a doctor.

Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing:

If swallowed, seek medical advice immediately and show this container or label.

Induce vomiting only, if affected person is fully conscious.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing agents:**CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

(Contd. on page 3)

Trade name: Osmo Country Color

(Contd. of page 2)

For safety reasons unsuitable extinguishing agents:

Water with full jet

5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters

Protective equipment:

Mouth respiratory protective device.

Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.

Ensure adequate ventilation

6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Warm water and cleansing agent

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep receptacles tightly sealed.

Keep away from heat and direct sunlight.

Use only in well ventilated areas.

Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Store in a cool location.

Store only in the original receptacle.

Information about storage in one common storage facility:

Do not store together with alkalis (caustic solutions).

Do not store together with oxidising and acidic materials.

Further information about storage conditions:

Keep container tightly sealed.

(Contd. on page 4)

Material Safety Data Sheets
according to 1907/2006/EC, Article 31

Printing date 23.05.2018

Version number 23

Revision: 08.05.2018

Trade name: Osmo Country Color

(Contd. of page 3)

7.3 Specific end use(s)

Store receptacle in a well ventilated area.
Protect from frost.
Protect from heat and direct sunlight.
No further relevant information available.

SECTION 8: Exposure controls/personal protection**Additional information about design of technical facilities:**

No further data; see item 7.

8.1 Control parameters**Ingredients with limit values that require monitoring at the workplace:****aliphatic hydrocarbons, C10-C13**

TWA (8 H)	Long-term value: 1.000 mg/m ³ , 150 ppm ppm Source: UK SIA
-----------	--

Additional information:

The lists valid during the making were used as basis.

8.2 Exposure controls**Personal protective equipment:****General protective and hygienic measures:**

Immediately remove all soiled and contaminated clothing
Avoid contact with the eyes and skin.
Do not eat, drink, smoke or sniff while working.
Do not carry product impregnated cleaning cloths in trouser pockets.

Respiratory protection:

Use suitable respiratory protective device only when aerosol or mist is formed.
Not necessary if room is well-ventilated.
Short term filter device:

Filter A/P2

Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Nitrile rubber, NBR

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact gloves made of the following materials are suitable:

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 6).

As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR

(Contd. on page 5)

Material Safety Data Sheets
 according to 1907/2006/EC, Article 31

Printing date 23.05.2018

Version number 23

Revision: 08.05.2018

Trade name: Osmo Country Color

(Contd. of page 4)

Eye protection: If risk of splashing:
 Safety glasses according to EN 166:2001 (e.g. densely closing frame glasses with side protection)

Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form: Fluid

Colour: According to product specification

Odour: Mild

Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: > 180 °C (DIN 51751)

Flash point: ≥ 63 °C (DIN 53213)

Ignition temperature: 240 °C

Auto-ignition temperature: Product is not selfigniting.

Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

Explosion limits:

Lower: 0.6 Vol %

Upper: 7.0 Vol %

Vapour pressure: 3 hPa [20°C]

Density at 20 °C: 1.05 - 1.30 g/cm³ (DIN 51757)

Solubility in / Miscibility with water:

Not miscible or difficult to mix.

Viscosity:

Dynamic: Not determined.

Kinematic at 20 °C: 40-80 s (DIN 53211/4)
>21 mm²/s (40°C)

Solvent separation test: < 3 % (ADR 2.2.1.4f)

9.2 Other information

No further relevant information available.

(Contd. on page 6)

Material Safety Data Sheets
 according to 1907/2006/EC, Article 31

Printing date 23.05.2018

Version number 23

Revision: 08.05.2018

Trade name: Osmo Country Color

(Contd. of page 5)

SECTION 10: Stability and reactivity

10.1 Reactivity	No further relevant information available.
10.2 Chemical stability	
Thermal decomposition / conditions to be avoided:	No decomposition if used and stored according to specifications.
10.3 Possibility of hazardous reactions	Reacts with fabric soaked in the product (e.g. cleaning wool). Reacts with acids, alkalis and oxidising agents.
10.4 Conditions to avoid	No further relevant information available.
10.5 Incompatible materials:	No further relevant information available.
10.6 Hazardous decomposition products:	Formation of toxic gases is possible during heating or in case of fire. Carbon monoxide and carbon dioxide Nitrogen oxides (NOx)
Additional information:	Warning: Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition)

SECTION 11: Toxicological information**11.1 Information on toxicological effects**

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:**aliphatic hydrocarbons, C10-C13**

Oral	LD50	> 5000 mg/kg (rat) (OECD 401)
Dermal	LD50	> 5000 mg/kg (rat) (OECD 402)
Inhalative	LC50 / 4h	21 mg/l (rat) (OECD 403)

Primary irritant effect:

Skin corrosion/irritation	At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.
Serious eye damage/irritation	Based on available data, the classification criteria are not met.
Respiratory or skin sensitisation	Based on available data, the classification criteria are not met.
CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)	
Germ cell mutagenicity	Based on available data, the classification criteria are not met.
Carcinogenicity	Based on available data, the classification criteria are not met.
Reproductive toxicity	Based on available data, the classification criteria are not met.
STOT-single exposure	Based on available data, the classification criteria are not met.
STOT-repeated exposure	Based on available data, the classification criteria are not met.

(Contd. on page 7)

Trade name: Osmo Country Color

(Contd. of page 6)

Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

aliphatic hydrocarbons, C10-C13

EC50 / 48h	> 1000 mg/l (daphnia) (OECD 202)
EC50/ 72h	> 1000 mg/l (algae) (OECD 201)
LC50 / 96h	> 1000 mg/l (fish) (OECD 203)
Biolog. Abbaubarkeit	(leicht abbaubar)

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

Additional ecological information:

General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue

08 01 11	waste paint and varnish containing organic solvents or other dangerous substances
15 01 10	packaging containing residues of or contaminated by dangerous substances

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN-Number

ADR, ADN, IMDG, IATA

Void

(Contd. on page 8)

Material Safety Data Sheets
according to 1907/2006/EC, Article 31

Printing date 23.05.2018

Version number 23

Revision: 08.05.2018

Trade name: Osmo Country Color

(Contd. of page 7)

14.2 UN proper shipping name ADR, ADN, IMDG, IATA	Void
14.3 Transport hazard class(es) ADR, ADN, IMDG, IATA Class	Void
14.4 Packing group ADR, IMDG, IATA	Void
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user	Not applicable.
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
Transport/Additional information:	Not dangerous according to the above specifications.
UN "Model Regulation":	Void

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulations:**

VOC (EC) < 400 g/l (VOC-max. Cat A/e (2010) = 400 g/l)

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases H304 May be fatal if swallowed and enters airways.**Department issuing SDS:** product safety department**Contact:** Hr. Dr. Starp

Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent

(Contd. on page 9)

Material Safety Data Sheets
according to 1907/2006/EC, Article 31



Printing date 23.05.2018

Version number 23

Revision: 08.05.2018

Trade name: Osmo Country Color

(Contd. of page 8)

PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Asp. Tox. 1: Aspiration hazard – Category 1

GB