

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

Junckers Rustic Oil Product no. 550, 559-561, 563-565, 568, 572-573, 576 REACH registration number Not applicable

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture Oil treatment of wood Uses advised against

The full text of any mentioned and identified use categories are given in section 16

1.3. Details of the supplier of the safety data sheet

Company and address

Junckers Industrier A/S Vaerftsvej 4 4600 Koege Denmark Tel. +45 70 80 30 00 Contact person

E-mail

productsafety@junckers.dk SDS date 2020-10-12 SDS Version 8.1

1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service). See section 4 "First aid measures".

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Not classified according to Regulation (EC) No. 1272/2008 (CLP)

2.2. Label elements

Hazard pictogram(s) Not applicable Signal word

Hazard statement(s) Not applicable Precautionary statements General -Prevention -Response -Storage -Disposal -



Identity of the substances primarily responsible for the major health hazards Not applicable

Additional labelling

Repeated exposure may cause skin dryness or cracking. (EUH066) Contains Phthalic anhydride. May produce an allergic reaction. (EUH208) Safety data sheet available on request. (EUH210) Unique formula identifier (UFI)

2.3. Other hazards

This product contains an organic solvent. Repeated or prolonged exposure to organic solvents may result in adverse effects to the nervous system and internal organs such as liver and kidneys. Additional warnings

Not applicable

VOC (volatile organic compound) VOC-Max: 450 g/l, MAXIMUM VOC CONTENT (A/i (SB)): 500 g/l.

SECTION 3: Composition/information on ingredients

3.1/3.2. Substances/Mixtures

NAME: IDENTIFICATION NOS.: CONTENT: CLP CLASSIFICATION: NOTE:	Hydrocarbons, C12-C15, n-alkanes, isoalkanes, < 2 % aromatics EC-no: 940-727-9 20-35% Asp. Tox. 1 H304, EUH066 O
NAME: IDENTIFICATION NOS.: CONTENT: CLP CLASSIFICATION: NOTE:	Hydrocarbons, C11-C12, isoalkanes, < 2 % aromatics EC-no: 918-167-1 REACH-no: 01-2119472146-39 5-15% Flam. Liq. 3, Asp. Tox. 1, Aquatic Chronic 4 H226, H304, H413, EUH066 O
NAME: IDENTIFICATION NOS.: CONTENT: CLP CLASSIFICATION: NOTE:	Hydrocarbons, C11-C13, isoalkanes, < 2 % aromatics EC-no: 920-901-0 REACH-no: 01-2119456810-40 2.5-<5% Asp. Tox. 1 H304, EUH066 O
NAME: IDENTIFICATION NOS.: CONTENT: CLP CLASSIFICATION: NOTE:	Hydrocarbons, C11-C14, isoalkanes, cyclics, < 2 % aromatics EC-no: 927-285-2 REACH-no: 01-2119480162-45 2.5-<5% Asp. Tox. 1 H304, EUH066 O
NAME: IDENTIFICATION NOS.: CONTENT: CLP CLASSIFICATION:	Phthalic anhydride CAS-no: 85-44-9 EC-no: 201-607-5 Index-no: 607-009-00-4 <0.15% Acute Tox. 4, Skin Irrit. 2, Skin Sens. 1, Eye Dam. 1, Resp. Sens. 1, STOT SE 3 H302, H315, H317, H318, H334, H335

(*) See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available. O = Organic solvent.

Other information

ATEmix(inhale, vapour) > 20 ATEmix(dermal) > 2000 ATEmix(oral) > 2000 N chronic (CAT 4) Sum = Sum(Ci/(M(chronic)i*25)*0.1*10^CAT4) = 0,35712 - 0,53568

SECTION 4: First aid measures



4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. The doctor can contact The National Poisons Information Service: Dial 0344 892 0111 (24 h service). Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Bring the person into fresh air and stay with him/her.

Skin contact

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with soap and water. Skin cleanser can be used. DO NOT use solvents or thinners.

Eye contact

Remove contact lenses. Flush eyes immediately with plenty of water or isotonic water (20-30 °C) for at least 15 minutes and continue until irritation stops. Make sure to flush under the upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.

Ingestion

Provide plenty of water for the person to drink and stay with him/her. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the victim lean forward with head down to avoid inhalation of- or choking on vomited material.

Burns

Not applicable

4.2. Most important symptoms and effects, both acute and delayed

This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms include headache, dizziness, tingling sensations of skin, difficulty in concentrating, tiredness. This product contains substances that may trigger an allergic reaction to predisposed persons. Sensitisation: This product contains substances, which may produce an allergic reaction through inhalation. The allergic reaction is typically taking place within an hour subsequent to exposure. The reaction results in an inflammatory reaction to the lungs.

4.3. Indication of any immediate medical attention and special treatment needed

Nothing special

Information to medics

Bring this safety data sheet.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Recommended: Alcohol-resistant foam, carbonic acid, powder, water mist. Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous catabolic substances are produced. These are: Carbon oxides. Fire will result in dense black smoke. Exposure to combustion products may harm your health. Fire fighters should wear appropriate protection equipment. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

- 6.1. Personal precautions, protective equipment and emergency procedures No specific requirements.
- 6.2. Environmental precautions
- No specific requirements.
- 6.3. Methods and material for containment and cleaning up



Use sand, sawdust, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations. To the extent possible cleaning is performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section on "Disposal considerations" in regard of handling of waste. See section on 'Exposure controls/personal protection' for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

See section on 'Exposure controls/personal protection' for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Always store in containers of the same material as the original container.

Storage temperature

No data available

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

OEL

Phthalic anhydride

Long-term exposure limit (8-hour TWA reference period): - ppm | 4 mg/m³ Short-term exposure limit (15-minute reference period): - ppm | 12 mg/m³ Comments: Sen (Sen = Capable of causing respiratory sensitisation.)

Hydrocarbons, C11-C14, isoalkanes, cyclics, < 2 % aromatics Long-term exposure limit (8-hour TWA reference period): - ppm | 1000 mg/m³ Short-term exposure limit (15-minute reference period): - ppm | - mg/m³

Hydrocarbons, C11-C13, isoalkanes, < 2 % aromatics Long-term exposure limit (8-hour TWA reference period): - ppm | 1000 mg/m³ Short-term exposure limit (15-minute reference period): - ppm | - mg/m³

Hydrocarbons, C11-C12, isoalkanes, < 2 % aromatics Long-term exposure limit (8-hour TWA reference period): - ppm | 1000 mg/m³ Short-term exposure limit (15-minute reference period): - ppm | - mg/m³

Hydrocarbons, C12-C15, n-alkanes, isoalkanes, < 2 % aromatic... Long-term exposure limit (8-hour TWA reference period): - ppm | 1000 mg/m³ Short-term exposure limit (15-minute reference period): - ppm | - mg/m³

DNEL / PNEC

No data available

8.2. Exposure controls

Compliance with the accepted occupational exposure limits values should be controlled on a regular basis. **General recommendations**

Smoking, eating and drinking are not allowed in the work premises.

Exposure scenarios

In the event exposure scenarios are appended to the safety data sheet, the operational conditions and risk management measures in these shall be complied with.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

Airborne gas and dust concentrations must be kept at a minimum and below current limit values (see above). Installation of an exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure emergency eyewash and -showers are clearly marked.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.



Measures to avoid environmental exposure

No specific requirements.

Individual protection measures, such as personal protective equipment



Use only CE marked protective equipment.

Respiratory Equipment

In case of insufficient ventilation: Use respiratory equipment with gas filter type A.

Skin protection

Wear appropriate protection clothing, e.g. coveralls in polypropylene approved type 6 and Category III. Hand protection

Nitrile rubber

Eye protection

Wear safety glasses with side shields.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

9.1. Information on basic physical and chemical properties	
Form	Liquid
Colour	Various colours
Odour	Mild
Odour threshold (ppm)	No data available
pH	No data available
Viscosity (40°C)	25-65 mm²/s
Density (g/cm ³)	0,88-0,98
Phase changes	
Melting point (°C)	No data available
Boiling point (°C)	No data available
Vapour pressure	No data available
Decomposition temperature (°C)	No data available
Evaporation rate (n-butylacetate = 100)	No data available
Data on fire and explosion hazards	
Flash point (°C)	> 60
Ignition (°C)	No data available
Auto flammability (°C)	No data available
Explosion limits (% v/v)	No data available
Explosive properties	No data available
Solubility	
Solubility in water	Insoluble
n-octanol/water coefficient	No data available
9.2. Other information	
Solubility in fat (g/L)	No data available

SECTION 10: Stability and reactivity

Nothing special

10.1. Reactivity No data available 10.2. Chemical stability The product is stable under the conditions, noted in the section "Handling and storage". 10.3. Possibility of hazardous reactions Nothing special 10.4. Conditions to avoid



10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Substance: Phthalic anhydride Species: Rat Test: LD50 Route of exposure: Oral Result: 1530 mg/kg

Skin corrosion/irritation

No data available

Serious eye damage/irritation

No data available

Respiratory or skin sensitisation

This product contains substances that may trigger an allergic reaction to predisposed persons. Sensitisation: This product contains substances, which may produce an allergic reaction through inhalation. The allergic reaction is typically taking place within an hour subsequent to exposure. The reaction results in an inflammatory reaction to the lungs.

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT-single exposure

No data available

STOT-repeated exposure

No data available

Aspiration hazard

No data available

Long term effects

This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms include headache, dizziness, tingling sensations of skin, difficulty in concentrating, tiredness.

SECTION 12: Ecological information

12.1. Toxicity

No data available

12.2. Persistence and degradability

Substance	
Phthalic anhydride	
Hydrocarbons, C1	
Hydrocarbons, C1	
Hydrocarbons, C1	
Hydrocarbons, C12	2-C15, n-alkan

degradability	Test	Result
i	Modified MITI Test	85 %
	Manometric Resp. Test	77,6 %
	Manometric Resp. Test	31,3 %
	Manometric Resp. Test	31,3 %
•	Manometric Resp. Test	71 %

LogPow

1.6

12.3. Bioaccumulative potential

Substance Phthalic anhydride

hydride

Potential bioaccumulation No **BCF** 3,4

12.4. Mobility in soil

Phthalic anhydride: Log Koc= 1,34544, Calculated from LogPow (High mobility potential). **12.5. Results of PBT and vPvB assessment**

Bio

Yes

Yes No

No Yes

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

12.6. Other adverse effects



This product contains substances, which may cause adverse long-term effects to the aquatic environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product is not covered by regulations on dangerous waste.

- Waste EWC code
- 08 01 12

waste paint and varnish other than those mentioned in 08 01 11

- Specific labelling
- Not applicable Contaminated packing

No specific requirements.

SECTION 14: Transport information

14.1 – 14.4

Not dangerous goods according to ADR, IATA and IMDG.

14.1. UN number	-
14.2. UN proper shipping name	-
14.3. Transport hazard class(es)	-
14.4. Packing group	-
Notes	-
Tunnel restriction code	-
IMDG	
UN-no.	-
Proper Shipping Name	-
Class	-
PG*	-
EmS	-
MP**	-
Hazardous constituent	-
IATA/ICAO	
UN-no.	-
Proper Shipping Name	-
Class	-
PG*	-

14.5. Environmental hazards

14.6. Special precautions for user

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code No data available

(*) Packing group (**) Marine pollutant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered. **Demands for specific education**



Additional information

Not applicable

Seveso

Biocidal reg. no.

Not applicable

Sources

Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.

Directive 2004/42/CE of the European Parliament and of the Council of 21 April 2004 on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products and amending Directive 1999/13/EC.

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677. The Stationery Office, 2002.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (CLP).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H413 May cause long lasting harmful effects to aquatic life.
- EUH066 Repeated exposure may cause skin dryness or cracking.

The full text of identified uses as mentioned in section 1

Additional label elements

Not applicable

Other

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The safety data sheet is validated by

ULS

Date of last essential change (First cipher in SDS version) 2020-08-28(8.0) Date of last minor change (Last cipher in SDS version)