

# SAFETY DATA SHEET

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

#### **Trade name**

Worktop Oil

Product no.

#### **REACH** registration number

Not applicable

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Relevant identified uses of the substance or mixture

wood surfaces, indoors

## Uses advised against

The full text of any mentioned and identified use categories are given in section 16

#### 1.3. Details of the supplier of the safety data sheet

#### Company and address

WOCA Denmark A/S

Tværvej 6

6640 Lunderskov

Denmark

Tel: +45 99585600 Fax:+45 99585636

## Contact person

LFH

#### E-mail

info@wocadenmark.com

#### **SDS** date

2018-03-26

#### **SDS Version**

4.0

## 1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service). See section 4 "First aid measures".

#### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

Not classified according to Regulation (EC) No. 1272/2008 (CLP)

#### 2.2. Label elements

## Hazard pictogram(s)

Not applicable

Signal word

-

## Hazard statement(s)

Not applicable-

## Safety statement(s)

General Prevention Response Storage Disposal -



#### Identity of the substances primarily responsible for the major health hazards

Not applicable

#### 2.3. Other hazards

Contains drying oils. Risk of self-ignition. Spills, soiled rags, etc. must be contained, stored in fire-proof waste containers and then destroyed.

This product contains an organic solvent. Repeated or prolonged exposure to organic solvents may result in adverse effects to the nervous system and internal organs such as liver and kidneys.

#### Additional labelling

Safety data sheet available on request. (EUH210)

#### **Additional warnings**

Not applicable

VOC

VOC-MAX: 290 g/l, MAXIMUM VOC CONTENT (A/i (SB)): 500 g/l.

## **SECTION 3: Composition/information on ingredients**

#### ▼3.1/3.2. Substances/Mixtures

NAME: Alkanes, C12-15-branched and linear

IDENTIFICATION NOS.: CAS-no: 1437281-03-2 EC-no: 940-727-9 REACH-no: 012120083064-61

CONTENT: 25-40% CLP CLASSIFICATION: Asp. Tox. 1, H304, EUH066

NOTE: S

NAME: Naphtha (petroleum), hydrotreated heavy

IDENTIFICATION NOS.: CAS-no: 64742-48-9 RÉACH-no: 01-2119457273-39

CONTENT: 1 - <2.5% CLP CLASSIFICATION: Asp. Tox. 1 H304, EUH066

NOTE: S

(\*) See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

S = Organic solvent

#### Other information

ATEmix(inhale, vapour) > 20 ATEmix(oral) > 2000

## **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

#### **General information**

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. The doctor can contact The National Poisons Information Service (dial 111, 24 h service).

Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

#### **Inhalation**

Bring the person into fresh air and stay with him/her.

#### Skin contact

Immediately remove contaminated clothing and shoes. Ensure that skin, which has been exposed to the material, is washed thoroughly with soap and water. Skin cleanser can be used. DO NOT use solvents or thinners.

#### Eye contact

Remove contact lenses. Flush eyes immediately with plenty of water or isotonic water (20-30°C) for at least 15 minutes and continue until irritation stops. Make sure to flush under the upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.

#### Ingestion

Provide plenty of water for the person to drink and stay with him/her. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the victim lean forward with head down to avoid inhalation of or choking on vomited material.



#### **Burns**

Not applicable

## 4.2. Most important symptoms and effects, both acute and delayed

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Nothing special

## Information to medics

Bring this safety data sheet.

## **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

Recommended: alcohol-resistant foam, carbonic acid, powder, water mist. Waterjets should not be used, since they can spread the fire.

## 5.2. Special hazards arising from the substance or mixture

Nothing special

#### 5.3. Advice for firefighters

No specific requirements.

#### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

No specific requirements.

## 6.2. Environmental precautions

No specific requirements.

## 6.3. Methods and material for containment and cleaning up

Use sand, sawdust, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations. To the extent possible cleaning is performed with normal cleaning agents. Avoid use of solvents.

## 6.4. Reference to other sections

See section on "Disposal considerations" in regard of handling of waste. See section on 'Exposure controls/personal protection' for protective measures.

## **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

Due to the danger of self-ignition, any waste from the product (spills, soiled rags etc.) are to be kept in a fire-proof place in air-tight containers, alternatively the waste can be burned. See section on 'Exposure controls/personal protection' for information on personal protection.

## 7.2. Conditions for safe storage, including any incompatibilities

Always store in containers of the same material as the original container.

### Storage temperature

Store frost-free.

## 7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2

#### SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

#### **OEL**

Alkanes, C12-15-branched and linear Long-term exposure limit (8-hour TWA reference period): 150 ppm | 1000 mg/m³ Short-term exposure limit (15-minute reference period): - ppm | - mg/m³

#### **DNEL / PNEC**

No data available



#### 8.2. Exposure controls

Compliance with the accepted occupational exposure limits values should be controlled on a regular basis.

#### **General recommendations**

Smoking, eating and drinking are not allowed in the work premises

## **Exposure scenarios**

In the event exposure scenarios are appended to the safety data sheet, the operational conditions and risk management measures in these shall be complied with.

#### **Exposure limits**

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

## Appropriate technical measures

Airborne gas and dust concentrations must be kept at a minimum and below current limit values (see above). Installation of an exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure emergency eyewash and -showers are clearly marked.

#### Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

#### Measures to avoid environmental exposure

No specific requirements.

#### Individual protection measures, such as personal protective equipment



#### Generally

Use only CE marked protective equipment.

#### **Respiratory Equipment**

If ventilation at the work place is insufficient, use a half- or full mask with an appropriate filter or an airsupplied breathing apparatus depending on the specific work situation and how long you will be using the product.

#### Skin protection

Wear appropriate protection clothing, e.g. coveralls in polypropylene approved type 6 and Category III.

No data available.

No data available.

No data available.

#### **Hand protection**

Recommended: Nitrile rubber. See the manufacturer's instructions.

#### Eve protection

Wear safety glasses with side shields.

## **SECTION 9: Physical and chemical properties**

## ▼9.1. Information on basic physical and chemical properties

Liquid Form Colour Various colours Odour Faint Odour threshold (ppm) No data available. pН No data available. 30-40 DIN CUP 4 Viscosity (40°C) Density (g/cm<sup>3</sup>) 0,9-1,1 Phase changes Melting point (°C) No data available. Boiling point (°C) No data available.

Evaporation rate (n-butylacetate = 100)

▼ Data on fire and explosion hazards

Decomposition temperature (°C)

Vapour pressure

Flash point (°C) >85
Ignition (°C) No data available.
Auto flammability (°C) No data available.
Explosion limits (% v/v) No data available.
Explosive properties No data available.

#### According to EC-Regulation 2015/830



#### **Solubility**

Solubility in water n-octanol/water coefficient

9.2. Other information

Solubility in fat (g/L)

Insoluble No data available.

No data available.

#### **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

No data available

#### 10.2. Chemical stability

The product is stable under the conditions, noted in the section "Handling and storage".

### 10.3. Possibility of hazardous reactions

Nothing special

#### 10.4. Conditions to avoid

Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

## 10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

## 10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

## **SECTION 11: Toxicological information**

#### 11.1. Information on toxicological effects

#### **Acute toxicity**

Substance: Naphtha (petroleum), hydrotreated heavy

Species: Rat Test: LD50

Route of exposure: Oral Result: >5000mg/kg

Substance: Naphtha (petroleum), hydrotreated heavy

Species: Rat Test: LD50

Route of exposure: Dermal

Result: >2000mg/kg

Substance: Naphtha (petroleum), hydrotreated heavy

Species: Rat Test: LC50

Route of exposure: Inhalation Result: >5000mg/m3/4h

Substance: Alkanes, C12-15-branched and linear

Species: Rat Test: LD50

Route of exposure: Oral Result: > 5000 mg/kg

Substance: Alkanes, C12-15-branched and linear

Species: Rabbit Test: LD50

Route of exposure: Dermal Result: > 5000 mg/kg

## Skin corrosion/irritation

No data available.

## Serious eye damage/irritation

No data available.

## Respiratory or skin sensitisation

No data available.

#### Germ cell mutagenicity

No data available.

#### Carcinogenicity

No data available.

Reproductive toxicity



No data available.

## STOT-single exposure

No data available.

#### **STOT-repeated exposure**

No data available.

#### **Aspiration hazard**

No data available.

#### Long term effects

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

## **SECTION 12: Ecological information**

#### 12.1. Toxicity

Substance: Naphtha (petroleum), hydrotreated heavy

Species: Fish Test: LL50 Duration: 96h Result: >1000mg/l

Substance: Naphtha (petroleum), hydrotreated heavy

Species: Daphnia Test: EL50 Duration: 48h Result: >1000mg/l

Substance: Naphtha (petroleum), hydrotreated heavy

Species: Algae Test: EL50 Duration: 72h Result: >1000mg/l

## 12.2. Persistence and degradability

Substance Biodegradability Test Result

No data available.

#### 12.3. Bioaccumulative potential

Substance Potential bioaccumulation LogPow BCF

No data available.

## 12.4. Mobility in soil

No data available

## 12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

#### 12.6. Other adverse effects

Nothing special

## **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Product is not covered by regulations on dangerous waste.

Waste

**EWC** code

Specific labelling

## Contaminated packing

No specific requirements.

## **SECTION 14: Transport information**

#### 14.1 - 14.4

Not dangerous goods according to ADR, IATA and IMDG.

### According to EC-Regulation 2015/830



#### ADR/RID

14.1. UN number
14.2. UN proper shipping name
14.3. Transport hazard
class(es)
14.4. Packing group
Notes
Tunnel restriction code

#### **IMDG**

UN-no.
Proper Shipping Name
Class
PG\*
Em S
MP\*\*
Hazardous constituent

#### IATA/ICAO

UN-no. Proper Shipping Name Class PG\*

#### 14.5. Environmental hazards

\_

## 14.6. Special precautions for user

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available

(\*) Packing group

(\*\*) Marine pollutant

## **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## Restrictions for application

People under the age of 18 shall not be exposed to this product cf. Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

## **Demands for specific education**

-

## **Additional information**

Not applicable

#### Seveso

\_

#### **Sources**

Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.

Directive 2004/42/CE of the European Parliament and of the Council of 21 April 2004 on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products and amending Directive 1999/13/EC.

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677. The Stationery Office, 2002

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (CLP). EC regulation 1907/2006 (REACH).

## 15.2. Chemical safety assessment



No

#### **SECTION 16: Other information**

## Full text of H-phrases as mentioned in section 3

H304 - May be fatal if swallowed and enters airways.

EUH066 - Repeated exposure may cause skin dryness or cracking.

The full text of identified uses as mentioned in section 1

## Additional label elements

Not applicable

#### Other

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The safety data sheet is validated by

LFH

Date of last essential change (First cipher in SDS version) 2017-12-13(3.0)

Date of last minor change (Last cipher in SDS version) 2017-12-13

ALPHAOMEGA. Licens nr.:3603101272, 6.4.1.0 www.chymeia.com