

Product Data Sheet



4510/Neu – 4598/000 : 1 Component Woodfillers

Code	Description	Code	Description
4510/Neu	Natural	4581/300	Dark Mahogany
4541/000	Cream	4581/800	Medium Mahogany
4542/000	White	4582/100	Light Oak
4551/000	Ash	4582/200	Medium Oak
4552/000	Cherry	4888/000	Teak
4559/000	Beech	4590/000	Medium Walnut
4572/000	Black	4598/000	Antique Pine

Technical Data	<p>A range of ready for use waterbased fillers developed for filling pin holes, nail holes and other small imperfections on wood for internal use. They are formulated to be applied by either knife or scraper.</p> <p>For hand application the softer 47 – Hand Stopper range is recommended. The standard range consists of a selection of the most widely used wood colours.</p> <p>This range is not suitable for repairing damaged edges or corners.</p>
Properties	Formulated on careful selection of quality raw materials, they have good adhesion/anchorage properties coupled with minimal shrinkage or absorption. They are quick drying with excellent sanding properties.
Cleaning	Equipment can be easily cleaned with hot water.
Application Guidelines	<ul style="list-style-type: none"> Apply the filler directly on to the timber using either a knife or scraper. It should applied slightly proud of the surface to allow for any shrinkage during drying Deep holes should not be filled in one operation, as this can lead to excessive shrinkage causing the filler to crumble. Overnight drying should be allowed for thorough hardening The excess dried filler should then be sanded flat with 180 – 240 grit lubricated sandpaper. The surface is then ready for normal polishing processes.
Important Information	<ul style="list-style-type: none"> Care must be exercised in selecting the appropriate filler to match the timber to which it is applied. Failure to give the filler adequate drying can result in film defects and shrinkage after the lacquering process. Product should be stored above 5°C and protected from frost. Optimum application is achieved between 18°C and 22°C with good air movement and ventilation. Finished products should not be subjected to environments with temperatures of < 2°C. Out of scope with 2004/42/EC.



Morrells Woodfinishes Ltd. Wellington Works, Mill Lane, Woodley, Stockport, Cheshire. SK6 1RN
Tel: 08705 60 61 62 Fax: 08705 604 604 Email: enquiries@morrells.co.uk Web: www.morrells.co.uk

Registered Office: Morrells Woodfinishes Limited. Company no. 785935 VAT. Reg No GB 712 5048 66



Health & Safety	Reference should be made to the appropriate MSDS for this product range, which can be found at www.morrells.co.uk The use of appropriate personal protection equipment (PPE) is recommended. These products are intended for professional use only.
----------------------------	--

The information provided on this information sheet is based on the best of our knowledge and experience, is given in good faith and should only be regarded as recommendations. No guarantee should be inferred and customers are advised to carry out their own tests under local conditions.

For further technical information contact our Technical Support Team on 0161 406 5300.



Morrells Woodfinishes Ltd. Wellington Works, Mill Lane, Woodley, Stockport, Cheshire. SK6 1RN
Tel: 08705 60 61 62 Fax: 08705 604 604 Email: enquiries@morrells.co.uk Web: www.morrells.co.uk

Registered Office: Morrells Woodfinishes Limited. Company no. 785935 VAT. Reg No GB 712 5048 66

