



TECHNICAL DATA SHEET

REVIN B3

Single component class D3 vinyl adhesive



0,5 Kg

DESCRIPTION

Single component adhesive in a watery dispersion for gluing pre-finished wood floors and floating laminate floors. When dry, the bonding achieves a D3 class resistance to water D3 (in compliance with EN 204).

TECHNICAL DATA CHEMICAL-PHYSICAL CHARACTERISTICS at 20°C (indicative values not constituting product specifications):

Open time (minutes)	8/12
Stability and storage (in original, unopened containers stored in a cool, dry place) (months)	12
Standard packaging (Kg)	0,5

APPLICATION

For lasting and effective adhesion, the subfloor must satisfy the following requirements:

- moisture below or equal to 2% measured in depth with a carbide hygrometer;
- absence of hygroscopic lightening material in the screed and adequate insulation if these materials are contained in the underlying layers;
- absence of moving cracks or other obvious faults.

Before laying the floor, it is also necessary to check that the moisture of the wood corresponds with that of the environment.

Apply REVIN B3 around the perimeter of the planks using the nozzle provided in every pack. Lay the planks pressing hard and "tapping" them to allow them to settle properly.

NOTES

Do not apply the product below 10°C or above 30°C.

Store above freezing.

Safety precautions. Keep the product in a tightly closed, upright container in a cool place away from sources of heat. The product is classified and coded in compliance with EC Directives/regulations concerning hazardous substances. The information for the user is given in the relevant safety sheet. Empty containers or those containing slight traces of the product must be disposed of in accordance with local regulations. VerMeister S.p.A. guarantees that the details given in this sheet are provided to the best of the company's technical-scientific knowledge and experience; however, the company cannot be held responsible in any way for the results obtained with the products as the conditions of application are beyond the company's control. It is always advisable to check the suitability of the product to each specific circumstance. This sheet cancels and replaces all previous editions.