

Premium
ultra thick
natural
rubber
underlay
with vapour
barrier

# ■ Stability you can rely on

TimberTech2 Gold's heavy mass stability is exceptional, preventing movement in your flooring to keep it looking good longer.

### Quiet please...

With its ultra-thick laminated materials TimberTech Gold has outstanding acoustic performance to make any room more comfortable.

# ■ Protects against damp

Gold vapour barrier gives superior protection against moisture rising up from the sub-floor – so your room stays dry.

Technical Data			
Properties	Unit	Value	Method
Density	kg/m³	950 <u>+</u> 50	internal
Weight per square metre	kg/m²	3.1 <u>+</u> 0.31	internal
Impact Sound Reduction	dB	<u>~</u> 23	BS EN ISO 717-2
Thermal Conductivity measured at 10°C	W/m k	0.036	DIN 4108
Thermal Resistance	Tog	0.53	BS4745:2005 (ISO 5085-1:1989)
Maximum Compression Load	kN/m²	2-5	DIN EN 1606

**QA Flooring Solutions Ltd** 

Unit 2 Hurricane Drive Liverpool L24 8RL Tel: 0151 495 3434 Fax: 0151 427 0484

Email: sales@qaflooring solutions.com

www.qaflooringsolutions.com

The information given above may vary and is partly based on information from our suppliers. It represents the prevailing level of expertise and is not binding in a legal sense. The compliance of legal requirements lies within the customers own responsibility.

Simply Better

Heavy Traffic

Wood





#### **Best for**

Cushioning

Moisture Protection Sound Reduction

Level Floors Compression Recovery

Underfloor Heating

Hard Wearing Heat Insulation Commercial Use\*

\*Suitable for hotels and public buildings

#### **Available in**

Code	QAU-TTG-01
Size	1m x 10m (10m <sup>2</sup> )
Thickness	3.3mm