


























SANDING RECOMMENDATION PALLMANN SPIDER

Requirement / Abrasive / Abrasive color	Coarse	Standard			Fine
	CERAMIC PLUS 178 MM	CERAMIC PLUS 178 MM	ZIRCON 178 MM	SILICON CARBID 178 MM	SILICON CARBID 178 MM
					
PALLMANN-Item No.	83655	83903	62003	83905	83906
Raw wood	for uneven floors				
Oiled wood floor surface					recommended
Sealed wood floor surface	for stubborn seals				
Remarks / Recommendation					
Exhaust pad (75685)					
Intermediate disc (79602)					
Support pad (75683)					
Power reserve	yes	yes	yes	optional	optional
Additional weight	1	1	1	1	1
Rotation speed	75 %	50 - 75 %	50 %	25 - 50 %	25 - 50 %

If you have any questions please contact your PALLMANN technical manager.

SANDING RECOMMENDATION PALLMANN GECKO FLEX

Requirement / Abrasive / Abrasive color	Coarse	Standard	Optional	Standard	Fine
	CERAMIC PLUS 178 MM 	CERAMIC PLUS 178 MM 	ZIRCON 178 MM 	SILICON CARBID 178 MM 	SILICON CARBID 178 MM 
PALLMANN-Item No.	83655	83903	62003	83905	83906
Raw wood	for uneven floors				
Oiled wood floor surface					recommended
Sealed wood floor surface	for stubborn seals				
Remarks / Recommendation					
Rotation speed	4 – 5	4 – 5	2 – 3	2 – 3	2 – 3

If you have any questions please contact your PALLMANN technical manager.