



# YUKON CLW 172

## PRODUCT DETAILS










|                    |                    |
|--------------------|--------------------|
| Article Number     | LTCLW2102-172      |
| Dimensions         | 1210 x 172 x 5 mm  |
| Weight per Package | 16.2 kg            |
| Area per Package   | 2.1 m <sup>2</sup> |
| Unit per Package   | 0 m <sup>2</sup>   |
| Area per pallet    | 104 m <sup>2</sup> |

Click 5 mm

## FACTS

|                     |                            |
|---------------------|----------------------------|
| Design              | Wood design                |
| Range               | Luxury Tiles               |
| Collection          | Click 5 mm Wood Collection |
| Joint               | Click5G                    |
| Floor heating       | Yes                        |
|                     | 5 mm                       |
| ColourCode          | 2                          |
| Installation method | Floating                   |

## TECHNICAL PROPERTIES

|                                  |                 |                               |   |
|----------------------------------|-----------------|-------------------------------|---|
| Reaction To Fire                 | EN13501- Bfl-s1 | 1                             |    |
| Thermal Resistance R-Value       | 0.032 (m2K/W)   |                               |    |
| Residual indentation             | EN ISO 24343-1  | < 0.2 mm (*with underlayment) |    |
| Dimensional stability            | EN ISO 23999    | < 0.1 %                       |  |
| Colour fastness                  | EN ISO 105-B02  | ≥ 6                           |  |
| Slip resistance                  | EN 13893        | DS (>0.3)                     |  |
| Statical electrical propensity   | EN 1815         | < 2 kV (antistatic)           |  |
| Scratch resistance               | EN16094         | Pass with good results        |  |
| Chemical resistance              | EN ISO 26987    | Pass with good results        |  |
| Resistance to bacteria and fungi | Good            |                               |   |

## Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.



## Other products in this collection



Wentwood - Click 5 mm



Redwood - Click 5 mm



Schwarzwald - Click 5 mm




Niagara - Click 5 mm



Kannur - Click 5 mm



Saxon - Click 5 mm



Belluno - Click 5 mm



Oulanka - Click 5 mm



Yukon - Click 5 mm



Sarek - Click 5 mm



Taiga - Click 5 mm



Whinfell - Click 5 mm

## Descriptions & Imagery

*All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.*

