

Bona Freshen Up

Technical data sheet

Freshen Up is a ready-to-use waterborne maintenance coating for the frequent maintenance and protection of varnished wooden floors. Being based on a pure polyurethane dispersion it leaves an exceptionally durable wear layer on the floor making it suitable for use in both domestic and commercial environments. Bona Freshen Up is high gloss and gives dull floors new shine and lustre.

- Specifically designed for varnish wooden floors
- Based on durable polyurethane
- Contains no waxes and thus allows for future applications of professional varnish.
- Meets EN 14904:2006 and DIN 18032:2 for slip resistance.

Technical data

Binding agent:	Polyurethane
Sheen:	Hi-gloss
Dilution:	Do not dilute, product is ready-to-use
Drying time:	~2 hours (20°C/60% RH)
Application tools:	Flat polish application pad
Coverage:	~50 m ² /litre
Safety:	Unclassified, see safety data sheet for more details.
Cleaning:	Clean tools in soap and water. Dried stains can be removed with Bona Remover or acetone.
Shelf life:	2 years, from date of production, in unopened original container
Storage/Transport:	The temperature must not fall below +5°C or exceed +25°C during storage and transport.
Disposal:	Wastes and emptied containers should be handled in accordance with local regulations.
Pack size:	10 x 1 litre (50 boxes per pallet) 3 x 5 litres (44 boxes per pallet)

Preparations

Remove loose dirt and grit from your floor. Clean floor thoroughly with Bona Cleaner to make sure that dirt will not be trapped in the coating. Let floor dry completely before applying Bona Freshen Up. Do not use Bona Freshen Up on any floor that has been waxed or oiled. Wax and oil residues will prevent the proper adhesion of Bona Freshen Up to the floor. **It is recommended to always test the adhesion to the surface and check for desired results prior to using Bona Freshen Up.**

Application

1. Shake container thoroughly before use. Apply Bona Freshen Up in a 3-4 cm wide wavy line on a 3 m² section of the floor and spread the product directly using a flat polish application pad. For best results, apply a thin consistent coat.
2. Without adding more product, smooth out the section by pulling the applicator along the grain of the wood.
3. Continue with next section and then allow the ready treated floor minimum 2 hours drying time before resuming light foot traffic on the floor. If required, it is possible to apply a second layer of Freshen Up after this time.

Avoid heavy traffic and the replacement of furniture and rugs until next day. To achieve a uniform aspect it is advised to always treat the entire surface.

Floor Care



Bona[®]

Bona Freshen Up

Technical data sheet

Floor Care



Maintenance

Wetcleaning of the floor may be resumed after three days. For regular cleaning use Bona Cleaner. Do not use strongly alkaline cleaning agents as they may damage the floor or remove the protective coating of Freshen Up.

In contrast to floors treated with polish, wax or similar material, a floor maintained with Freshen Up can still be overcoated with professional varnish. Prior to application of varnish, the surface must be treated with the Bona Prep System using screen P150 to remove build up from previous applications of Bona Freshen Up. For more overcoating instructions see the product data for Bona Prep at www.bona.com.

Tips

- When smoothing out the product, keep the applicator pad flat to the surface, going wall-to-wall. Avoid lifting the applicator along the way as this produces bubbles.
- Do not work into areas starting to dry as this may produce streaking.
- If applying multiple layers of Freshen Up. Do not stress the drying time between coats. Risk of dissolving previous layers.