Material Safety Datasheet

AS PER REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL

Section 1 - Identification of the	substance/mixture and of the company/undertaking		
1.1 Product identifier			
Product name	Granguard BP		
1.2 Relevant identified uses of the substance or mixture and uses advised against			
Description Binding primers			
1.3 Details of the supplier of the	e safety data sheet		
Company	Granwax Products Limited		
Address	West Street Riddings Alfreton Derbyshire DE55 4EW		
Web	www.granwax.com		
Email	info@granwax.com		
Email address of the competent person	info@granwax.com		
1.4 Emergency telephone num	ber		
Emergency telephone number	+ 44 (0)1773 541177 - 9.00 am - 5.00 pm Monday to Friday		
Section 2 - Hazards identificati	on		
2.1 Classification of the substar	nce or mixture		
2.1.1 Classification - 1999/45/EC	Xn; R20-65 Xi; R36/37-43 N; R51/53 R10-66 Symbols: Xn: Harmful. N: Dangerous for the environment.		
Main hazards	Flammable. Harmful by inhalation. Irritating to eyes and respiratory system. May cause sensitisation by skin contact. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking.		
2.1.2. Classification - EC 1272/2008	Flam. Liq. 3: H226; Asp. Tox. 1: H304; Skin Sens. 1: H317; Eye Irrit. 2: H319; STOT SE 3: H335; STOT SE 3: H336; Aquatic Chronic 2: H411;		
2.2 Label elements			
Hazard pictograms			
Signal word	Danger		

Hazard statement	 Flam. Liq. 3: H226 - Flammable liquid and vapour. Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways. Skin Sens. 1: H317 - May cause an allergic skin reaction. Eye Irrit. 2: H319 - Causes serious eye irritation. STOT SE 3: H335 - May cause respiratory irritation. STOT SE 3: H336 - May cause drowsiness or dizziness. Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting
Precautionary Statement: Prevention	effects. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 - Keep container tightly closed. P240 - Ground/bond container and receiving equipment. P241 - Use explosion-proof electrical/ventilating/lighting// equipment. P242 - Use only non-sparking tools. P243 - Take precautionary measures against static discharge. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash with clean water thoroughly after handling. P271 - Use only outdoors or in a well-ventilated area. P272 - Contaminated work clothing should not be allowed out of the workplace. P273 - Avoid release to the environment. P280 - Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary Statement: Response	 P301+P310 - IF SWALLOWED: IF SWALLOWED: Immediately call a POISON CENTER/doctor/. P302+P352 - IF ON SKIN: Wash with plenty of water/. P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 - Call a POISON CENTER/doctor/ /if you feel unwell. P321 - Specific treatment (see on this label). P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention. P370+P378 - In case of fire: Use to extinguish. P391 - Collect spillage.
Precautionary Statement: Disposal	P501 - Dispose of contents/container to requirements of local authority

Material Safety Datasheet

Page 3 of 11

2.3 Other hazards							
Other hazards	No data is available on this product.						
Section 3 - Composition/inform	nation on ing	gredients					
3.2. Mixtures							
67/548/EEC / 1999/45/EC							
Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Aromatic polyisocyanate		127821-00-5			10 - 20%	Xi; R36-43	
Aromatic polyisocyanate		53317-61-6			10 - 20%	Xi; R36-43	
Hydrocarbon C9 aromatic			918-668-5		30 - 40%	Xn; R65 Xi; R37 N; R51/53 R10-66-67	
Aromatic polyisocyanate concentration		103051-64-5			10 - 20%	Xi; R43	
Xylene isomer mixture 20% ethylbenzene (Xylene, o-,m-,-p-or mixed isomers)		1330-20-7	215-535-7		1 - 10%	Xn; R20/21-48/20-65 Xi; R36/37/38 R10	
2-methoxy-1-methylethyl acetate (1-Methoxypropylacetate)	607-195-00-7	108-65-6	203-603-9		10 - 20%	R10	
Butylated Hydroxy toluene (2,6-Di-tert-butyl-p-cresol)		128-37-0	204-881-4		0 - 0.5%	N; R50/53	
EC 1272/2008		•				•	·
Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Aromatic polyisocyanate		127821-00-5			10 - 20%	Skin Sens. 1: H317; Eye Irrit. 2: H319;	
Aromatic polyisocyanate		53317-61-6			10 - 20%	Skin Sens. 1: H317; Eye Irrit. 2: H319;	
Hydrocarbon C9 aromatic			918-668-5		30 - 40%	Flam. Liq. 3: H226; Asp. Tox.1: H304; STOT SE 3: H335; STOT SE 3: H336; Aquatic Chronic 2: H411;	
Aromatic polyisocyanate concentration		103051-64-5			10 - 20%	Skin Sens. 1: H317;	
Xylene isomer mixture 20% ethylbenzene (Xylene, o-,m-,-p-or mixed isomers)		1330-20-7	215-535-7		1 - 10%	Flam. Liq. 3: H226; Asp. Tox. 1: H304; Acute Tox. 4: H312; Skin Irrit. 2: H315; Eye Irrit. 2: H319; Acute Tox. 4: H332; STOT SE 3: H335; STOT RE 2: H373;	
2-methoxy-1-methylethyl acetate (1-Methoxypropylacetate)	607-195-00-7	108-65-6	203-603-9		10 - 20%	Flam. Liq. 3: H226;	

Section 4 - First aid measures			
4.1 Description of first aid mea	sures		
Inhalation	Move the exposed person to fresh air.		
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open.		
Skin contact	Wash off immediately with plenty of soap and water. Remove contaminated clothing.		
Ingestion	DO NOT INDUCE VOMITING.		
4.2 Most important symptoms	and effects, both acute and delayed		
Inhalation	Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system.		
Eye contact	May cause irritation to eyes.		
Skin contact	May cause irritation to skin.		
Ingestion	Ingestion may cause nausea and vomiting.		
4.3 Indication of any immediate	e medical attention and special treatment needed		
Inhalation	If you feel unwell, seek medical advice (show the label where possible).		
Eye contact	Seek medical attention.		
Skin contact	Seek medical attention if irritation or symptoms persist.		
Ingestion	If you feel unwell, seek medical advice (show label where possible).		
Section 5 - Firefighting measur	res		
5.1 Extinguishing media			
	Use extinguishing media appropriate to the surrounding fire conditions.		
5.2 Special hazards arising from the substance or mixture			
	Burning produces irritating, toxic and noxious fumes.		
5.3. Advice for firefighters			
	Wear self contained breathing apparatus and protective clothing.		
Section 6 - Accidental release	measures		
6.1 Personal precautions, protective equipment and emergency procedures			
	Ensure adequate ventilation of the working area. Avoid contact with skin and eyes.		
6.2 Environmental precautions			
	Do not allow product to enter drains. Prevent further spillage if safe.		

6.3 Methods and material for containment and cleaning up		
Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.		
See section 8. EXPOSURE CONTROLS / PERSONAL PROTECTION for further information. See section 13. DISPOSAL CONSIDERATIONS for further information.		
je		
ng		
Ensure adequate ventilation of the working area. Avoid contact with eyes and skin. Adopt best Manual Handling considerations when handling, carrying and dispensing.		
7.2 Conditions for safe storage, including any incompatibilities		
Keep containers tightly closed. Keep in a cool, dry, well ventilated area. Store in correctly labelled containers.		
7.3 Specific end use(s)		
See section 1.2. Relevant identified uses of the substance or mixture and uses advised against for further information.		

Material Safety Datasheet

Page 6 of 11

Section 8 - Exposure controls/personal protection

8.1 Control parameters				
	Occupational exposure controls.			
8.1.1 Exposure Limit Values				
2-methoxy-1-methylethyl acetate (1-Methoxypropylacetate)	WEL 8-hr limit ppm: WEL 15 min limit ppm: WEL 8-hr limit mg/m ³ total inhalable dust: WEL 8-hr limit mg/m ³ total respirable dust:	50 100 - -	WEL 8-hr limit mg/m ³ : WEL 15 min limit mg/m ³ : WEL 15 min limit mg/m ³ total inhalable dust: WEL 15 min limit mg/m ³ total respirable dust:	274 548 - -
Butylated Hydroxy toluene (2,6-Di-tert-butyl-p-cresol)	WEL 8-hr limit ppm: WEL 15 min limit ppm: WEL 8-hr limit mg/m ³ total inhalable dust: WEL 8-hr limit mg/m ³ total respirable dust:	- -	WEL 8-hr limit mg/m ³ : WEL 15 min limit mg/m ³ : WEL 15 min limit mg/m ³ total inhalable dust: WEL 15 min limit mg/m ³ total respirable dust:	10 - -
Xylene isomer mixture 20% ethyilbenzene (Xylene, o-,m-,-p-or mixed isomers)	WEL 8-hr limit ppm: WEL 15 min limit ppm: WEL 8-hr limit mg/m ³ total inhalable dust: WEL 8-hr limit mg/m ³ total respirable dust:		WEL 8-hr limit mg/m3: WEL 15 min limit mg/m ³ : WEL 15 min limit mg/m ³ total inhalable dust: WEL 15 min limit mg/m ³ total respirable dust:	220 441 - -
8.2 Exposure controls				
8.2.1 Appropriate engineering controls	Ensure adequate ventilation	on of the	e working area.	
8.2.2 Individual protection measures	Wear protective clothing.			
Eye / face protection	Approved safety goggles.			
Skin protection - Handprotection	Chemical resistant gloves (PVC).			
Skin protection - Other	Wear suitable protective clothing.			
Respiratory protection	Respiratory protection must be used during use (A1 or A2EN41).			l41).
Occupational exposure controls	Keep away from food, drink and animal feedstuffs.			

Material Safety Datasheet

Page 7 of 11

Section 9 - Physical and chemical properties		
9.1 Information on basic physical and chemical properties (continued)		
Appearance	Liquid	
Colour	Clear	
Odour	Pungent	
Odour threshold	No data available	
pH	No data available	
Melting point	No data available	
Freezing point	No data available	
Initial boiling point	≈ 140°C	
Flash point	40°C	
Evaporation rate	No data available	
Flammability (solid, gas)	No data available	
Vapour pressure	No data available	
Vapour density	No data available	
Relative density	± 0.984 (H ₂ O = 1 @ 20°C)	
Fat Solubility	No data available	
Partition coefficient	= 100 log P	
Autoignition temperature	No data available	
Viscosity	15	
Explosive properties	No data available	
Oxidising properties	No data available	
Solubility	Insoluble in water	
9.2 Other information		
Conductivity	No data is available	
Surface tension	No data is available	
Gas group	No data is available	
Benzene Content	No data is available	
Lead content	No data is available	
VOC (Volatile organic compounds)	582 g/l	

Material Safety Datasheet

Page 8 of 11

Section 10 - Stability and reactivity		
10.1 Reactivity		
	Stable under normal conditions.	
10.2 Chemical stability		
	Stable under normal conditions.	
10.3 Possibility of hazardous re	actions	
	No data is available on this product.	
10.4 Conditions to avoid		
	No data is available on this product.	
10.5 Incompatible materials		
	No data is available on this product.	
10.6 Hazardous decomposition	products	
	No data is available on this product.	
Section 11 - Toxicological inforr	nation	
11.1 Information on toxicologica	al effects	
Skin corrosion/irritation	May cause irritation to skin.	
Serious eye damage/irritation	May cause irritation to eyes.	
11.1.4 Toxicological Information		
	No data available	
Section 12 - Ecological informa	tion	
12.1 Toxicity		
	No data is available on this product.	
12.2 Persistence and degradab	ility	
	No data is available on this product.	
12.3 Bioaccumulative potential		
Bioconcentration factor (BCF)	No data is available on this product.	
Octanol-Water Partition Coefficient	100 log P	
12.4 Mobility in soil		
	No data is available on this product.	
12.5 Results of PBT and vPvB	assessment	
	No data is available on this product.	
12.6 Other adverse effects		
	No data is available on this product.	

Section 13 - Disposal considerations			
13.1 Waste treatment methods			
	Dispose of in compliance with all local and national regulations.		
Castion 11 Transport informati			
Section 14 - Transport informati	Of		
Hazard pictograms			
	PLAMMABLE 3		
14.1 UN number			
	UN1263		
14.2 UN proper shipping name			
	Paint		
14.3. Transport hazard class(es	3)		
ADR/RID	3		
Subsidiary risk	-		
IMDG	3		
Subsidiary risk	-		
IATA	3		
Subsidiary risk	-		
14.4 Packing group			
Packing group	111		
14.5 Environmental hazards			
Environmental hazards	No		
Marine pollutant	No		
14.6 Special precautions for user			
	No data is available on this product.		
14.7 Transport in bulk according	g to Annex II of MARPOL 73/78 and the IBC Code		
	No data is available on this product.		
ADR/RID			
Hazard ID	30		
Tunnel Category	(D/E)		
IMDG			
EmS Code	F-E S-E		

ΙΑΤΑ	
Packing Instruction (Cargo)	366
Maximum quantity	220 L
Packing Instruction (Passenger)	355
Maximum quantity	60 L
Section 15 - Regulatory informa	ition
	mental regulations/legislation specific for the substance or mixture
Regulations	REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC. COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/105/EC, 93/105/EC, 93/105/EC and 2000/21/EC.

Material Safety Datasheet

Page 11 of 11

Section 16 - Other information	
Other information	
Revision	This document differs from the previous version in the following areas: None
Text of risk phrases in Section 3	R10 - Flammable R20/21 - Harmful by inhalation and in contact with skin. R36/37/38 - Irritating to eyes, respiratory system and skin. R36 - Irritating to eyes. R37 - Irritating to respiratory system.
Further information	
	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.

Copyright 2020 Granwax Products Limited

Granguard BP - MSDS

Issue date: 18 August 2020



Tele: 01773 541177 Email: info@granwax.com Web: www.granwax.com