



Master Care

For lacquered, vinyl/LVT and laminate floors

Technical Data Sheet

21.10.2021 - p. 1/2

Care for your vinyl floor, laminate floor or lacquered wood floor using Master Care. This care product smoothens small scratches, increases the resistance of the surface and provides effective protection against wear. This extends the lifetime of the surface or floor. Because Master Care does not build up a thick coating, you can use the product whenever it is required.

- **Care treatment to refresh floors**
- **Extends the lifetime of the floor**
- **Protects against wear and scratches**
- **Easy to use**
- **IBR-certified**



Application area

For all types of vinyl, laminate, PVC and lacquered/painted surfaces.

Work description

Preparation	<p>Wash the floor thoroughly with WOCA Intensive Wood Cleaner, until the surface is perfectly clean. Wash with clean water afterwards. Leave the floor to dry completely before application of Master Care.</p> <p>Always remember to test on a less visible spot to check the compatibility of the surface with the product.</p>
Treatment	<p>Shake the container well before use.</p> <p>Apply the concentrated care product as a thin, even coat. If the cloth/mop becomes dirty, rinse in clean water and wring thoroughly. Then continue the application. Do not apply additional Master Care once a surface has begun to dry.</p> <p>Leave the floor to dry for approximately 30-60 minutes or until it is completely dry before use. No polishing or other treatment is required afterwards.</p>
Please note	<p>For best results, use WOCA Master Cleaner for regular cleaning of the treated surface.</p>

Drying time

Drying time	1-2 hours at 20°C
-------------	-------------------



Technical data

Declaration	Triisobutylphosphate. Can trigger allergic reaction.
Density	1.00-1.10 g/ml.
pH-value	pH 7-8
Shelf life	3 years
Application Temperature	+15-25°C and approx. 50% air humidity.
Coverage	60 m ² /L
Mixing ratio	Ready to use. Do not dilute.
Cleaning of tools	Use soap and water
Storage	+10-25°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.
VOC	VOC-Max: 30 g/l, MAXIMUM VOC CONTENT (A/i [WB]): 140 g/l.
Packaging	1 L
Re-treatment	2-4 times a year or when required.

Maintenance and related products

Weekly cleaning	Master Cleaner, #684510
Related products	Intensive Wood Cleaner, #551525

Contact

WOCA Denmark A/S
Tvæervej 6
DK - 6640 Lunderskov
T +45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.